



Baden-Württemberg
Regierungspräsidium Tübingen

INFORMATION



USE OF STEEL SHOT (according CIP regulations)

Gun requirements:

- The gun has to be in perfect working condition.
- Always stay within the proof marks (see chart with the column "GUN").
- Additional steel shot proofing on standard proofed guns, can only be done if they comply with the magnum load requirements.
- Magnum tests and steel shot tests have to be requested separately.
- If steel shot ammunition according to chart no.2 is being used, the gun has to have a choke not bigger than 0,5mm.

Ammunition requirements:

- Use only certified and accordingly marked ammunition, especially:
 - ammunition has to be superscripted with „steel shot“
 - magnum loaded ammunition need an extra mark.
- Always pay attention to the ricochet warnings.

CALIBER for guns with smooth bore	AMMUNITION USED		GUN <small>(sort and mark of test is signed with X)</small>		
	maximum allowed gas pressure [bar]	Steel Shot Ø [mm] chart I barrel without choke restriction	chart II barrel with max. 0,5mm choke (1/2-choke)	„Normal“ (standard) tested 	„Magnum“ tested with additional steel shot 
12/70 Normal Load	740	≤ 3,25		X	
12/70 Magnum Load	1050	≤ 4,00	> 4,00		X
12/76 Magnum Load					
16 Normal Load ^{*)}	780	≤ 3,00		X	
16 Magnum Load ^{*)}	1050	≤ 3,50	> 3,50		X
20/70 Normal Load	830	≤ 2,60		X	
20/70 Magnum Load	1050	≤ 3,25	> 3,25		X
20/76 Magnum Load					

^{*)} at present without legal regulation

VF_504_M_Info_Use-Of-Steel-Shot_19-01-05

Beschussamt Ulm
Albstraße 74

89081 Ulm

Tel.: ++49 (0)731 - 9 68 51 - 0
Fax: ++49 (0)731 - 9 68 51 - 99
beschussamt@rpt.bwl.de

Accredited Testing
Laboratory and
Certification Body
according ISO 17025 and EN 45011

